

“Nature Doesn’t Stand An Outside Chance.”



We’ve Created A New Level
“Permanent.”

EVOLUTION® by Miller Paint Co. Lifetime Warranty Exterior Coating

A high solids coating created with an advanced 100% pure acrylic co-polymer resin for prolonged adhesion. Formulated for properly prepared vertical wood, composite, metal, concrete, stucco and block. Evolution can be applied at a rate of 250 sq. ft. per gallon to yield 3 mils dry film thickness in one application. Evolution by Miller Paint saves labor, resources and is covered by our exclusive lifetime warranty.

- Advanced high-quality 100% pure acrylic system
- Easy to apply: Brush, roll or spray
- High film build
- Superior adhesion
- Mildew, mold & algae resistant
- Excellent flexibility
- Easy clean-up with just water



Specifications for Evolution – TECHNICAL AT-A-GLANCE

	Flat	Velvet	Satin
Product Number	8500	8900	8600
Volume Solids	47.4%	46.8%	45.4%
Viscosity	98-103 KU	98-103 KU	98-103 KU
Gloss	0-5%@60°	5-10%@60°	10-20%@60°

V. O. C. 75 (Flat), 75 (Velvet) and 90 (Satin) gms/liter minus water

COVERAGE: Approximately 250-400 square feet per gallon.
Properly prepared surfaces provide best coverage.

DRY TIME: Thirty minutes to touch @ 70° F and 50% relative humidity.
Two hours to recoat @ 70° F and 50% relative humidity.

www.millerpaint.com

1-800-852-3254

An Employee Owned Company

Specification figures should be taken as accurate for products being produced at the time of publication in untinted white bases only. Formulation improvements may be made from time to time that may affect these figures to some degree. Manufacturing tolerances of +/-2% are considered acceptable. Whenever a change is made that the Manufacturer considers substantial, the Specification will be revised.

Miller, Evolution, Evolution by Miller Paint Co., Inc. and Miller Paints are registered trademarks of Miller Paint Co., Inc. Portland, OR. 7/06 10K

