

Miller Kril™ – A CLASSIC 100% ACRYLIC PAINT

A classic, 100% acrylic, high-build exterior paint. It has strong adhesion, good durability and exceptional color retention. Kril is formulated to be mold and mildew resistant and is available in four sheens and an extensive color selection. It is ideal for any commercial or residential building, including those with wood, concrete, stucco, or manufactured siding. Kril's ease of application makes it the perfect paint for anyone from the average homeowner to the experienced professional.

- 100% Acrylic
- Excellent durability
- Excellent color retention
- Excellent adhesion
- Unlimited color selection
- Available in semigloss, satin, velvet and flat sheens
- Water clean up



Miller Kril is available in the following sheens:

SEMIGLOSS

This high-sheen product is very washable and perfect for areas that are more susceptible to dirt, grease and moisture. Use in applications like exterior smooth siding, exterior smooth wood trim, and primed metal surfaces.

SATIN

This finish will minimize dirt pick-up and is washable. Ideal for full body exterior work where some sheen is desired. Best used when the surface is free of major imperfections. Use in applications like exterior body, sidings (wood or metal), exterior rough or smooth trim.

VELVET

Ideal for projects where a deep, rich look is desired yet only a minimal sheen is needed. This finish has a minimal sheen that is mostly seen at an angle. It reduces dirt pick-up and provides some washability. Ideal for full body exterior work where some sheen is desired. Best used when the surface is free of major imperfections. Use in applications like exterior body, sidings (wood or metal), or exterior rough trim.

FLAT

A flat finish will minimize visibility of surface imperfections due to lack of light refraction. It is best used for rough surfaces or surfaces that are regularly repainted or touched up. Use in applications like exterior body, sidings (wood or metal), or exterior rough trim.

Specifications for Kril – TECHNICAL AT-A-GLANCE

	FLAT	VELVET	SATIN	SEMIGLOSS
Volume Solids	36.8%	35.8%	34.2%	31.7%
Viscosity	93-98 KU	95-100 KU	95-100 KU	95-100 KU
Weight Per Gallon	11.98#	11.0#	10.5#	10.3#
Gloss	0-5% @ 60° 0-5% @ 85°	5-10% @ 60° 7-15% @ 85°	10-20% @ 60° 30-45% @ 85°	45-55% @ 60°

V.O.C.

Less than 125 gm/liter minus water

COVERAGE:

Approximately 250–400 square feet per gallon

DRY TIME:

One hour to touch and four hours to recoat @ 70° F and 50% relative humidity

Specification figures should be taken as accurate for products being produced at the time of publication in untinted white bases only. Formulation improvements may be made from time to time that may affect these figures to some degree. Manufacturing tolerances of +/-2% are considered acceptable. Whenever a change is made that the Manufacturer considers substantial, the Specification will be revised.

